

STANDARD SPECIFICATIONS

Frequency Range	3.2 MHz -100.0 MHz
Frequency Tolerance (@ 25 °C)	± 50 ppm Standard (see Crystal Part Number Guide for more details)
Crystal Cut	AT (Standard) or BT
Resonance	Parallel (18pF Standard) (see Crystal Part Number Guide for more details)
Shunt Capacitance (Co)	7 pF max
Equivalent Series Resistance (Ω)	See Table
Frequency Stability over Operating Temperature	± 100 ppm Standard (see Crystal Part Number Guide for more details)
Drive Level	1 mW max
Aging	± 5 ppm max/ year
Operating Temperature. Range	0 °C ~+70 °C Standard (see Crystal Part Number Guide for more details)
Storage temperature Range	-40°C ~ +85°C Standard

Ordering Instructions (see Crystal Part Number Guide for more details)


Example: QVS Part # = QVS49S-21AFI18-20.000

QVS49S	±50ppm (@ 25°C)	±100ppm (Over Temp)	0°C~+70°C	Fundamental	Insulator Tab	Load Cap.	Freq.
	2	1	A	F	I	18pF	-20.000MHz

Maximum Standard Equivalent Series Resistance (Ω)

Frequency Range (MHz)	ESR (Ω)
Fundamental Mode	
3.200 ~ 3.500	300
3.501 ~ 4.000	200
4.001 ~ 5.000	150
5.001 ~ 6.000	120
6.001 ~ 7.000	100
7.001 ~ 9.000	80
9.001 ~ 13.000	60
13.001 ~ 20.000	40
20.001 ~ 30.000	30
Third Overtone Mode	
27.000 ~ 100.000	100

DIMENSIONS(Unit=mm)



QVS TECH INC

6965 El Camino Real, Ste 105 Carlsbad, CA 92009 Phone: 760-929-8677 Fax: 760-929-8077

email: sales@qvstech.com

Specifications subject to change without notice (Rev A)